




# PANEL5000-C17I-T

Touch Screen Monitor



17" SXGA Capacitive Touch Screen  
Industrial Monitor

## PANEL5000-CI7I-T




### Specifications:


General	Control button	Set Contrast ratio and Luminance via OSD at the back panel
	Dimensions (W x H x D)	428mm x 342mm x 57mm (16.85" x 13.46" x 2.24")
	Drill Hole Size (W x H)	411mm x 325mm (16.18" x 12.80")
	Box structure	Front panel: aluminum-magnesium alloy, anodized coating ;Back cover: SGCC, Ground isolation protection
	Mounting	Support Embedded, wall-mounted, Desktop and VESA mounting
	Power Supply	DC 12V, support reverse polarity protection, optional DC 24V
	Power Dissipation	12W
	Signal input	VGA & DVI-D
	NW	-
LCD	LCD Size	17" SXGA TFT
	Resolution	1280 x 1024
	Colors	16.7MB
	Active Area (W x H)	338mm x 270mm (13.31" x 10.63")
	Backlight	LED
	MTBF	30000hrs
	Pixel Pitch(H x V)	0.264 x 0.264
	Luminance	250cd/m <sup>2</sup>
	Contrast Ratio	1000 : 1
	Viewing Angle	(L) 85 / (R) 85 / (T) 80 / (B) 80
Touchscreen	Type	Multi-point capacitive touch screen
	Transmittance	> 75%
	Controller interface	USB
	Driver Support	Windows XP, Windows 7, Winows8, Windows 10, Linux
	Multi-touch	10 points (windows system)
	Surface Hardness	Mohs' Number 7
Environmental	Work Temperature	-20 ~ 60° C (-4 ~ 140 °F )
	Storage Temperature	-30 ~ 80° C (-22 ~ 176 °F )
	Relative humidity	5~95% (Non condensation)
	Shake	SSD applied: 1.5 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis
	Shock	SSD applied: 10 G, IEC 60068-2-64, Half-sine wave, 11ms duration
	EMC	CE/FCC Class A
	Water-proof	Front panel IP65

### Dimensions:

Unit : mm



### I/O:



Interface Definition:

- A:USB port
- B:DC IN(12V)
- C:DVI port
- D:VGA port

### Ordering Information:

Product Code	Description
PANEL5000-C171-T	17" TFT LCD/Capacitive Touch Screen/DC12V input/1280*1024
PANEL5000-C171-TW	17" TFT LCD/Capacitive Touch Screen/9~30V wide voltage input/1280*1024

### Optional Equipment:

VGA Cable	3M/5M
DVI Cable	3M/5M
USB Cable	3M/5M
Power Line	3M/5M
HDMI turn DVI	3M/5M

### Packing List:

Adapter	Adapter 12V/3.33A,40W 2pin Phoenix terminal
VGA Cable	1.8m
USB Cable	1.8m
Power Line	Chinese standard Power Line PSB-10+ST3
Hook	4*Hooks apply to Thickness=1mm~1.2mm