


3I610NX


3.5" SBC supports 6th / 7th Gen Intel® Skylake-U / Kaby Lake-U CPU
 VGA, HDMI, 4 x PoE, 1 x Intel Gb Ethernet,
 16DI / 16DO, 8 x USB, 2 x COM, 2 x Mini PCIe



Features:

- 6th / 7th Gen Intel® Skylake-U / Kaby Lake-U, i7 / i5 / i3 / Celeron CPU
- 2 x DDR4 SODIMM socket, Max. 32GB
- Multiple Independent display: VGA & HDMI
- 4 x PoE, 1 x Intel GbE LAN, 2 x USB 3.0, 6 x USB 2.0
- 2 x COM, 16DI / 16DO, 2 x Mini PCIe
- TPM 2.0 (Optional)

Dimensions: (Unit:mm)



Specifications :

- CPU
6th / 7th Gen Intel® Skylake-U / Kaby Lake-U, i7 / i5 / i3 / Celeron CPU
- MB Chipset
Intel® Skylake-U / Kaby Lake-U SoC
- Graphics
Intel® HD Graphics, Support DirectX 12 & OpenGL 4.4 / 4.5
- System Memory
2 x DDR4 1866 / 2133 MHz SODIMM, Max. 32GB
- Storage
1 x mini card socket for mSATA
2 x SATA ports 3.0 Data transfer rates up to 6.0 Gb/s (600 MB/s)
- BIOS
Insyde UEFI BIOS
- Display
1 x VGA, 1 x HDMI
- TPM
TPM 2.0 (Option)
- LAN
4 x Intel GbE I210IT (PoE) (external)
1 x Intel GbE I219LM (external)
- Expansion Interface
1 x Full size Mini PCIe (PCIe / mSATA / USB)
1 x Full size Mini PCIe (PCIe / USB 3.0 / USB2.0)

Expansion Module

Mini Card	GPS, 3G / 4G, WI-FI, 2 / 4 x LAN, 4 x COM, CANBus, SDI / AHD Video
By Cable	Bluetooth, Digital I/O, 2 / 4 PoE, 4 x USB mini card

- USB
2 x USB 3.0 (external) ; 6 x USB 2.0 (internal)
- Serial IO
2 x RS232 / 422 / 485 (internal)
- GPIO
Hardware digital Input & Output, 16 x DI / 16 x DO
- WDT
Hardware Watch Dog Timer, 0~255 sec programmable
- Power Input
Wide Range +9~36V
- Dimension
3.5" (146 x 102 mm)
- Operation Temperature
-20°C~70°C (100 % CPU Usage)
- Operation Humidity
5~95%, non-condensing
- Chassis (OEM I/O Expansion by request)
Box PC: SKY 3, TASK
- OS Support

7th Generation Intel® Core™ Processor family: Kaby Lake

Windows® 10 IOT (64bit)
 Ubuntu 16.04.3 above, Fedora 26 above, CentOS 7.4 above

6th Generation Intel® Core™ Processor family: Skylake

Windows® 10 IOT (64bit) / Windows® 8.1 (64bit)
 Windows® Embedded 8 Standard (64bit) / Windows® 7 (64bit)
 Windows® Embedded Sta 7 (64bit)
 Ubuntu 16.04.3 above, Fedora 26 above, CentOS 7.4 above