

SKY 2-2I640DW

Compact Fanless Embedded Computer
with Elkhart Lake ATOM® X6413E
/ J6413 Processor



■ Features:

- Elkhart Lake ATOM® X6413E / J6413 CPU
- 1 x DDR4 SODIMM socket, Max. 32GB
- Multiple Independent display: 2 x HDMI / DP, 1 x eDP
- 3 x Intel GbE LAN, 2 x USB 3.0, 2 x COM
- 2 x M.2, 4DI / 4DO (option), 1 x Nano SIM (option)

■ Specifications :

Motherboard	2I640DW
CPU	Intel® Elkhart Lake ATOM X6413E CPU Intel® Elkhart Lake Celeron J6413 CPU
Chipset	Intel Elkhart Lake SoC
Memory	1 x DDR4 SODIMM socket, Max. 32GB
Expansion slots	1 x M.2 B Key Type 2242 / 3042 (PCIe x2 / USB 3.0 / USB 2.0) 1 x M.2 B Key Type 2242 (PCIe x2 / USB 2.0) 1 x Nano SIM (option)
I/O ports	Network 3 x Intel GbE I210IT (external)-X6413E CPU or 3 x Intel GbE I211AT (external)-J6413 CPU USB 2 x USB 3.0 Serial ports 2 x RS232 / 422 / 485 Display 2 x HDMI or DP
Optional Modules & Accessory	GPS, Bluetooth, PoE, WiFi, 4G LTE, Isolated COM, battery UPS, DI / DO, Video Input *VESA / Wall Mounting Kit, DIN Rail Mounting Kit
OS Support	Windows® 10 IOT (64bit) Ubuntu 16.04.3 above, Fedora 26 above, CentOS 7.4 above

■ Mechanical

Dimensions	145W x 111.2D x 71.9H mm
Weight	1.36 kg
Mounting	DIN Rail Mount*, VESA / Wall Mount*


■ Power

DC input	Wide Range +9~36V
AC input	External adapter 100 / 240V (optional)

■ Environment

Operating Temp. (100 % CPU usage)	-20°C to +60°C
Storage Temp.	-20°C to +70°C
Relative Humidity	95% @ 40°C, non-condensing

■ Dimension



Specification are subject to change without prior notice. ODM / OEM is available.